

unimdf

with new, expanded product range



 UNILIN

unimdf

with new, expanded product range

Discover our wide product range

- 4 new, innovative MDF products
- more than 50 new stock references
- Standard range with 150 references, of which 106 can be supplied directly from stock

MDF for all your applications

- interior design
- stand construction
- shop interiors
- furniture
- profiles
- ...

Order now from our new product range and immediately enjoy these benefits:

- ✓ **Choose from a wide range of sizes, available in stock**
- ✓ **Choose from a wide range, including the lacquer specialties from Spano.**
- ✓ **Faster delivery time**
 - standard range available in stock (full truckload): 5 working days
 - standard range on request: 4 weeks
- ✓ **Flexible service**
 - standard range available in stock available per pack
 - standard range on request: available by full truck
 - combined order with chipboard and melamine: available subject to terms and conditions



uniMDF black

- Decorative high density MDF
- Mass-coloured in black
- Ideally suited for use in interiors and furniture
- Low formaldehyde emission similar to natural wood (NAF)




uniMDF black gloss

- Finished MDF with decorative and resistant surface
- Mass-coloured in black
- Transparent glossy finishing coat on both sides
- Self-adhesive protective film on both sides
- Low formaldehyde emission similar to natural wood (NAF)




uniMDF prime

- Paint-ready MDF for a perfect and economical finish
- with a white UV primer coating on both sides
- Ready for immediate painting in the desired final colour
- Excellent adhesion, with water-based paint
- Cost and time saving: less paint consumption and less painting work



uniMDF hydro prime

- Paint-ready moisture resistant MDF for a perfect and efficient finish
- with a white UV primer coating on both sides
- Ready for immediate painting in the desired final colour
- Excellent adhesion, with water-based paint
- Cost and time saving: less paint consumption and less painting work



Raw MDF



uniMDF comfort

- Standard MDF
- For general applications in dry conditions



uniMDF air

- Light MDF
- For general applications in dry conditions



uniMDF hydro comfort

- Moisture-resistant MDF
- For general applications in humid conditions
- Suitable for kitchen and bathroom



uniMDF hydro air

- Light, moisture-resistant MDF
- For general applications in humid conditions
- Suitable for plinths and mouldings



uniMDF fire comfort

- Fire retardant MDF
- Increased fire resistance (EN Fire Class B - s2, d0)
- For fire doors and fire walls, for example, in stairwells, elevator shafts, corridors, etc.

MDF TRADE LIST

| uniMDF comfort | | | | | | | | | | | | | | | kg/m ³ : 720 | |
|-----------------|-----|-----|-----|-----|----|----|----|----|----|-----|----|----|----|----|-------------------------|----|
| Thickness in mm | 3 | 4 | 6 | 8 | 9 | 10 | 12 | 15 | 16 | 18* | 19 | 22 | 25 | 28 | 30 | 38 |
| 1220x2440 | 240 | 200 | 138 | 104 | 88 | 84 | 68 | 56 | 52 | 44 | 44 | 36 | 32 | 28 | 25 | 20 |
| 1220x3050 | | | 99 | 88 | 88 | 72 | 68 | 56 | 52 | 44 | 44 | 36 | 32 | 28 | 24 | |
| 2070x2800 | | | 85 | 52 | | 52 | 44 | 36 | 34 | 30 | 30 | 24 | 20 | | | |
| 2070x4100 | | | | | | | 27 | | 22 | | 18 | | | | | |

| uniMDF air | | | | | | | | | | | | | | kg/m ³ : 600 | |
|-----------------|-----|-----|----|----|----|----|-----|----|----|----|----|----|----|-------------------------|--|
| Thickness in mm | 8 | 9 | 10 | 12 | 15 | 16 | 18* | 19 | 22 | 25 | 28 | 30 | 38 | | |
| 1220x2440 | 125 | 100 | 90 | 75 | 60 | 60 | 50 | 50 | 40 | 32 | 30 | 30 | 20 | | |
| 1220x3050 | 100 | 100 | 90 | 75 | 60 | 60 | 50 | 50 | 40 | 32 | 30 | 30 | 20 | | |
| 2070x2800 | | | | 48 | | 40 | 33 | 35 | 27 | | | | | | |
| 1310x3060 | | | | | | 52 | 44 | | | | | | | | |
| 1250x2500 | | | | | | | 55 | | | | | | | | |
| 1220x2750 | | 104 | | 80 | | 60 | 54 | | 44 | | | | | | |

| uniMDF hydro comfort | | | | | | | | | | | | | kg/m ³ : 720 | |
|----------------------|-----|----|----|----|----|----|-----|----|----|----|----|----|-------------------------|--|
| Thickness in mm | 6 | 9 | 10 | 12 | 15 | 16 | 18* | 19 | 22 | 25 | 28 | 30 | | |
| 1220x2440 | 132 | 88 | 80 | 68 | 52 | 52 | 44 | 40 | 36 | 32 | 28 | 30 | | |
| 1220x3050 | 99 | 88 | | 68 | 56 | 52 | 44 | 40 | 36 | 28 | | 24 | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

| uniMDF hydro air | | | | | | kg/m ³ : 600 | |
|------------------|----|----|-----|----|----|-------------------------|--|
| Thickness in mm | 12 | 15 | 18* | 22 | 38 | | |
| 1220x2440 | 75 | 60 | 50 | 40 | 20 | | |
| 1220x3050 | 75 | 60 | 50 | 36 | 20 | | |
| | | | | | | | |
| | | | | | | | |

| uniMDF fire comfort | | | | | | | kg/m ³ : 750 | |
|---------------------|----|----|----|-----|----|----|-------------------------|--|
| Thickness in mm | 9 | 12 | 15 | 18* | 19 | 22 | | |
| 1220x2440 | 88 | 68 | 56 | 44 | 40 | 36 | | |
| 1220x3050 | 88 | 68 | 56 | 44 | 40 | 36 | | |
| | | | | | | | | |
| | | | | | | | | |

| uniMDF prime | | | | | | kg/m ³ : 600 | |
|-----------------|----|----|----|-----|--|-------------------------|--|
| Thickness in mm | 9 | 12 | 16 | 18* | | | |
| 1220x2440 | 80 | 60 | 45 | 40 | | | |
| 1220x3050 | 80 | 60 | 45 | 40 | | | |
| | | | | | | | |
| | | | | | | | |

| uniMDF hydro prime | | | | | | kg/m ³ : 600 | |
|--------------------|-----|--|--|--|--|-------------------------|--|
| Thickness in mm | 18* | | | | | | |
| 1220x2440 | 40 | | | | | | |
| 1220x3050 | 40 | | | | | | |
| | | | | | | | |
| | | | | | | | |

| uniMDF black | | | | | | | kg/m ³ : 760 | |
|-----------------|----|----|----|-----|----|----|-------------------------|--|
| Thickness in mm | 9 | 12 | 16 | 18* | 19 | 25 | | |
| 1220x2440 | 75 | 60 | 44 | 40 | 37 | 29 | | |
| 1220x3050 | 60 | 48 | 35 | 31 | 30 | 23 | | |
| 2070x2800 | | | | 32 | 28 | | | |

| uniMDF black gloss | | | | | | kg/m ³ : 760 | |
|--------------------|-----|--|--|--|--|-------------------------|--|
| Thickness in mm | 18* | | | | | | |
| 1220x2440 | 40 | | | | | | |
| | | | | | | | |
| | | | | | | | |

| | |
|----------|--|
| x | Quantities per pack |
| | Available from stock per pack - delivery within 5 working days (for full truck) |
| | Available on request: delivery within 4 weeks (6 weeks for uniMDF fire comfort in 22 mm) |

18* Standard thickness